Stainless steel impact doors

Catalog reference configuration for double-acting traffic doors. Confirm the selected model, configuration and installation interface before ordering.



Catalog illustration

For repeated two-way passage

For facility teams, dealers and installers reviewing people and cart traffic. Single, double and unequal double-leaf arrangements are listed in our catalog.

COMPONENT	CATALOG STANDARD REFERENCE
Door panel	304 stainless steel, 0.8 mm
Door frame	304 stainless steel, 1.2 mm
Frame section	50 x 75 mm
Door leaf thickness	40 mm
Core	Aluminum alloy honeycomb
Hinge	Dedicated E-type eccentric shaft hinge
Observation window	Acrylic, standard 300 x 400 mm
Perimeter	Rubber sealing around the door leaf
Impact board	Black PE, 5 mm thick; 500 mm high
Hardware	Hinge and accessory set included

Configuration and evidence

Source: SHUANGLUAN METAL product catalog, page 5; arrangements on pages 4 and 7. The quotation and approved drawing define each order. Illustrations do not establish the material or size of another model.

Send a useful project brief

Provide opening width and height, wall thickness, photographs from both sides, quantity, destination, loaded cart dimensions and the required project documents. Use our companion buyer selection checklist.

Product selection, configuration, quotation and delivery coordination are supported by a manufacturing partner. This sheet does not establish a fire, hurricane, air-leakage or cleanroom rating, powered-vehicle impact suitability, stock, lead time or warranty.

sunlumedoor.com | shuangluan02@gmail.com | WhatsApp +86 189 8869 7788

佛山市双銮金属材料有限公司